

Note: This datasheet may be out of date

Please download the latest datasheet of BLM03HD471SN1# from the official website of Murata Manufacturing
Co. Ltd.

Co., Ltd.

https://www.murata.com/en-global/products/productdetail?partno=BLM03HD471SN1%23

BLM03HD471SN1#

"#" indicates a package specification code.








< List of part numbers with package codes >

BLM03HD471SN1D BLM03HD471SN1J BLM03HD471SN1B



Appearance & Shape











- 1. Horizontal winding inner coil structure enables low storage capacitance which result to high noise suppression performance up to 1GHz frequency range.
- 2. The small size of BLM03H series (0.6x0.3mm) is suitable for noise suppression in small equipment such as cellular phones.

■Application

- 1. Intra-system EMC in cellular phones.
- 2. EMI countermeasure of cellular phones.
- Keyed carrier noise countermeasure for cellular phones.
- 4. EMI countermeasure of NotePC/MID, and DSC



Other Usage

For general



Packaging Information

Packaging	Specifications	Minimum Order Quantity
D	180mm Paper Tape	15000
J	330mm Paper Tape	50000
В	Bulk(Bag)	1000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2019/09/05



Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=BLM03HD471SN1%23

Note: This datasheet may be out of date

Mass(typ.)

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ BLM03HD471SN1\# \ from \ the \ official \ website \ of \ Murata \ Manufacturing} }$

BLM03HD471SN1#

"#" indicates a package specification code.



Shape	SMD
Size Code (in mm)	0603
Size Code (in inch)	0201
Length	0.6mm
Length Tolerance	±0.03mm
Width	0.3mm
Width Tolerance	±0.03mm
Thickness	0.3mm
Thickness Tolerance	±0.03mm
Impedance (at 100MHz)	470Ω
Impedance (at 100MHz) Tolerance	±25%
Impedance (at 1GHz)	1000Ω
Impedance (at 1GHz) Tolerance	±40%
Rated Current (at 85°C)	175mA
Rated Current (at 125°C)	175mA
DC Resistance(max.)	1.3Ω
Operating Temperature Range	-55°C to 125°C

Number of Circuit	1

0.0003g

2 of 3

Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/09/05


^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


Note: This datasheet may be out of date. $\underline{ Please \ download \ the \ latest \ data sheet \ of \ BLM03HD471SN1\# \ from \ the \ official \ website \ of \ Murata \ Manufacturing} }$ Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=BLM03HD471SN1%23

BLM03HD471SN1#

"#" indicates a package specification code.







Impedance-Frequency Characteristics

Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

