

Capacitor > Ceramic Capacitor (Capacitor) > Ceramic Capacitor (SMD)

Automotive Chip Multilayer Ceramic Capacitors

Please be sure to read this before using the product.  
Precautions regarding counterfeit products

# GCM21BC71E475KE36 #

The '#' is the packaging code.


生産中 ?

パワートレイン
AEC-Q200
RoHS
REACH
125°C max.

リフローOK
7P-OK
?

<List of product numbers with packaging code>  
GCM21BC71E475KE36K GCM21BC71E475KE36L

## Appearance and shape



## spec

[Search for products with similar specifications](#) ?

L dimension	2.0 ± 0.2mm
W dimension	1.25 ± 0.2 mm
T dimension	1.25 ± 0.2 mm
Capacitance	4.7 μF ± 10%
Distance between external electrodes g	0.7mm min.
External electrode dimensions e	0.2-0.7mm
Operating temperature limit	-55 °C ~ 125 °C
Rated voltage	25Vdc
Size code mm	2012M
Capacitance change rate	± 22.0%
Temperature characteristics (compliant standard)	X7S (EIA)
Temperature range of temperature characteristics	-55 °C ~ 125 °C

## Product Search Assistant

We propose candidate products of the same size or smaller size with similar specifications.







- Small size
- High capacity
- High withstand voltage
- High temperature support
- Emphasis on DC bias characteristics
- Find a silicon capacitor with a similar capacity

## Reference information

Packaging code	specification	Standard packing quantity
K	330mm embossed taping	10000
L	180mm embossed taping	3000

Mass (typical value)	
1 piece	17.0mg
φ180mm reel	102g

## Characteristic data



[\(Simsurfing\) More detailed graph](#) ?

[Product inquiries](#)

[Sample inquiry](#)

[Inquiry for quotation](#)

[Technical inquiry](#)

[20pcs free sample](#)

[Agency / Web trading company \(inventory search\)](#)

[Download this page as PDF](#)

[How to read the product number](#) ➤

[Series details](#) ➤

### Detailed information

[Detailed spec sheet](#) ➤

- Rated value
- Performance and test method
- Packaging method
- Caution / Precautions for use (storage / mounting / land dimensions / cleaning / transportation, etc.)

### Product data

[SPICE Netlist \(mod format\)](#) ➤

[Sparameter \(S2P format\)](#) ➤

[Structural drawing](#) ➤

[Reliability test data \\* Representative data](#) ➤

Share this page



Contact Us

Official SNS



[Product information](#)

[Electronic components](#)

[solution](#)

[Completed equipment / others](#)

[application](#)

[support](#)

[FAQ](#)

[PDF download](#)

[Video library](#)

[Main base information](#)

[Inventory search](#)

[Product news](#)

[Technical article](#)

[my Murata](#)

[Event](#)

[Webinar](#)

[Special feature](#)



European RoHS / REACH compatible  
Compatible with California Proposition 65

We will explain the regulatory laws and regulations regarding chemical substances contained in products and our response to them.