





THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - BY - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS				
		P	LTR	DESCRIPTION	DATE	DWN APVD
H	-		V2	REFERENCE FOR OVERALL PITCH DIMENSION CORRECTED	09MAR2017	SS PS

PART NUMBER BOX PACKAGING	PART NUMBER REEL PACKAGING	NO OF POS "n"	DIMENSION "A" MAX
7-215083-4	215083-4	4	8,6
7-215083-6	215083-6	6	11,1
7-215083-8	215083-8	8	13,6
8-215083-0	1-215083-0	10	16,2
8-215083-2	1-215083-2	12	18,7
8-215083-4	1-215083-4	14	21,3
8-215083-6	1-215083-6	16	23,8
8-215083-8	1-215083-8	18	26,3
9-215083-0	2-215083-0	20	28,9
9-215083-4	2-215083-4	24	34,0



NOTES;


1. SHOWN IS A 10 POSITION CONNECTOR

2 FOR FLAT RIBBON CABLE REQUIREMENTS.
SEE APPLICATION SPEC 114-19016.

3 CONNECTOR-HEIGHT AFTER CABLE TERMINATION 5.1 mm AVERAGE.
DEPENDING ON PROCESSING, SEE APPLICATION SPEC 114-19016.

250 CONNECTORS PER BOX
BOX PACKAGING

2500 CONNECTORS PER REEL
REEL PACKAGING

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN P.V.Tongerren	-	 TE Connectivity	
DIMENSIONS: mm		CHK H SPELDE	24-08-01		
		APVD H SPELDE	24-08-01		
		PRODUCT SPEC	108-19052		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC	114-19016	NAME Micro-MaTch MALE-ON-WIRE CONNECTOR	
MATERIAL SEE TABLE		WEIGHT	-		
FINISH SEE TABLE		Customer Drawing	SCALE 5:1	SHEET 1 OF 1	REV V2