


Standard Rectifier

| | |
|-------------------------|----------|
| 3~ Rectifier | |
| V_{RRM} | = 1800 V |
| I_{DAV} | = 40 A |
| I_{FSM} | = 370 A |


3~ Rectifier Bridge


Part number

DMA40U1800GU



Backside: isolated

 E72873



Features / Advantages:

- Low forward voltage drop
- Planar passivated chips
- Easy to mount with one screw
- Space and weight savings

Applications:

- Supplies for DC power equipment
- Input rectifiers for PWM inverter
- Battery DC power supplies
- Field supply for DC motors

Package: GUPF

- Isolation Voltage: 2500 V~
- Industry standard outline
- RoHS compliant
- Epoxy meets UL 94V-0
- Soldering pins for PCB mounting
- Base plate: Plastic overmolded tab
- Reduced weight

Disclaimer Notice


Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.



| Rectifier | | | | Ratings | | | |
|------------|--|-----------------------------|-------------------|------------------------------|------|-----------------------------------|------------------|
| Symbol | Definition | Conditions | | min. | typ. | max. | Unit |
| V_{RSM} | max. non-repetitive reverse blocking voltage | | | | | 1900 | V |
| V_{RRM} | max. repetitive reverse blocking voltage | | | | | 1800 | V |
| I_R | reverse current | $V_R = 1800$ V | | $T_{VJ} = 25^\circ\text{C}$ | | 40 | μA |
| | | $V_R = 1800$ V | | $T_{VJ} = 150^\circ\text{C}$ | | 1.5 | mA |
| V_F | forward voltage drop | $I_F = 10$ A | | $T_{VJ} = 25^\circ\text{C}$ | | 1.06 | V |
| | | $I_F = 30$ A | | | | 1.28 | V |
| | | $I_F = 10$ A | | $T_{VJ} = 150^\circ\text{C}$ | | 0.92 | V |
| | | $I_F = 30$ A | | | | 1.23 | V |
| I_{DAV} | bridge output current | $T_C = 90^\circ\text{C}$ | rectangular | $T_{VJ} = 175^\circ\text{C}$ | | 40 | A |
| | | | $d = \frac{1}{3}$ | | | | |
| V_{FO} | threshold voltage | | | $T_{VJ} = 175^\circ\text{C}$ | | 0.74 | V |
| r_F | slope resistance | | | | | 16.3 | m Ω |
| | | | | | | } for power loss calculation only | |
| R_{thJC} | thermal resistance junction to case | | | | | 4.3 | K/W |
| R_{thCH} | thermal resistance case to heatsink | | | | 0.5 | | K/W |
| P_{tot} | total power dissipation | | | $T_C = 25^\circ\text{C}$ | | 35 | W |
| I_{FSM} | max. forward surge current | $t = 10$ ms; (50 Hz), sine | | $T_{VJ} = 45^\circ\text{C}$ | | 370 | A |
| | | $t = 8,3$ ms; (60 Hz), sine | | $V_R = 0$ V | | 400 | A |
| | | $t = 10$ ms; (50 Hz), sine | | $T_{VJ} = 150^\circ\text{C}$ | | 315 | A |
| | | $t = 8,3$ ms; (60 Hz), sine | | $V_R = 0$ V | | 340 | A |
| I^2t | value for fusing | $t = 10$ ms; (50 Hz), sine | | $T_{VJ} = 45^\circ\text{C}$ | | 685 | A ² s |
| | | $t = 8,3$ ms; (60 Hz), sine | | $V_R = 0$ V | | 665 | A ² s |
| | | $t = 10$ ms; (50 Hz), sine | | $T_{VJ} = 150^\circ\text{C}$ | | 495 | A ² s |
| | | $t = 8,3$ ms; (60 Hz), sine | | $V_R = 0$ V | | 480 | A ² s |
| C_J | junction capacitance | $V_R = 400$ V; $f = 1$ MHz | | $T_{VJ} = 25^\circ\text{C}$ | | 10 | pF |



| Package GUPF | | Ratings | | | | |
|---------------|--|----------------------|-------------------------------------|------|------|------|
| Symbol | Definition | Conditions | min. | typ. | max. | Unit |
| I_{RMS} | RMS current | per terminal | | | 70 | A |
| T_{VJ} | virtual junction temperature | | -40 | | 175 | °C |
| T_{op} | operation temperature | | -40 | | 150 | °C |
| T_{stg} | storage temperature | | -40 | | 150 | °C |
| Weight | | | | 8.5 | | g |
| M_D | mounting torque | | 0.8 | | 1.2 | Nm |
| F_C | mounting force with clip | | 20 | | 120 | N |
| $d_{Spp/App}$ | creepage distance on surface striking distance through air | terminal to terminal | 6.7 | 5.4 | | mm |
| $d_{Spb/Apb}$ | | terminal to backside | 10.0 | 8.0 | | mm |
| V_{ISOL} | isolation voltage | t = 1 second | | 2500 | | V |
| | | t = 1 minute | 50/60 Hz, RMS; $I_{ISOL} \leq 1$ mA | 2100 | | V |



Part description

- D = Diode
- M = Standard Rectifier
- A = (up to 1800V)
- 40 = Current Rating [A]
- U = 3- Rectifier Bridge
- 1800 = Reverse Voltage [V]
- GU = GUPF


| Ordering | Ordering Number | Marking on Product | Delivery Mode | Quantity | Code No. |
|----------|-----------------|--------------------|---------------|----------|----------|
| Standard | DMA40U1800GU | DMA40U1800GU | Tube | 14 | 514906 |

| Similar Part | Package | Voltage class |
|--------------|---------|---------------|
| DNA40U2200GU | GUPF | 2200 |
| GUO40-16NO1 | GUPF | 1600 |
| GUO40-12NO1 | GUPF | 1200 |
| GUO40-08NO1 | GUPF | 800 |

Equivalent Circuits for Simulation

* on die level

$T_{VJ} = 175^{\circ}C$




Rectifier


| | | | |
|--------------|--------------------|------|----|
| $V_{0\ max}$ | threshold voltage | 0.74 | V |
| $R_{0\ max}$ | slope resistance * | 13.7 | mΩ |



Outlines GUPF



| Dim. | Millimeter | | | Inches | | |
|-------------------|------------|-------|-------|-----------|-------|-------|
| | min | typ. | max | min | typ. | max |
| A | 5.40 | 5.50 | 5.60 | 0.213 | 0.217 | 0.221 |
| A2 | 3.90 | 4.00 | 4.10 | 0.154 | 0.158 | 0.162 |
| A3 | 0.95 | 1.00 | 1.10 | 0.037 | 0.039 | 0.043 |
| A4 | 0.95 | 1.00 | 1.05 | 0.037 | 0.039 | 0.041 |
| A5 | 1.60 | 1.70 | 1.80 | 0.063 | 0.067 | 0.071 |
| A6 | 1.25 | 1.30 | 1.35 | 0.049 | 0.051 | 0.053 |
| b | 0.95 | 1.00 | 1.05 | 0.037 | 0.039 | 0.041 |
| b2 | 1.95 | 2.00 | 2.05 | 0.077 | 0.079 | 0.081 |
| C | 0.45 | 0.50 | 0.55 | 0.018 | 0.020 | 0.022 |
| D | 24.80 | 25.00 | 25.20 | 0.977 | 0.985 | 0.993 |
| E | 34.70 | 35.00 | 35.30 | 1.367 | 1.379 | 1.391 |
| e | BSC 7.50 | | | BSC 0.296 | | |
| F | 2.40 | 2.50 | 2.60 | 0.095 | 0.099 | 0.102 |
| L | 20.30 | 20.40 | 20.50 | 0.800 | 0.804 | 0.808 |
| L1 | 3.70 | 3.75 | 3.80 | 0.146 | 0.148 | 0.150 |
| O | 17.40 | 17.50 | 17.60 | 0.686 | 0.690 | 0.693 |
| ØP | 4.10 | 4.20 | 4.30 | 0.162 | 0.165 | 0.169 |
| Q | 9.20 | 9.30 | 9.40 | 0.362 | 0.366 | 0.370 |
| $\frac{\phi}{2}R$ | | 1.77 | | | 0.070 | |
| s1 | 3.45 | 3.50 | 3.55 | 0.136 | 0.138 | 0.140 |
| s2 | 1.45 | 1.50 | 1.55 | 0.057 | 0.059 | 0.061 |
| t1 | 0.95 | 1.00 | 1.05 | 0.037 | 0.039 | 0.041 |
| t2 | 0.95 | 1.00 | 1.05 | 0.037 | 0.039 | 0.041 |
| x1 | 3.20 | 3.30 | 3.40 | 0.126 | 0.130 | 0.134 |
| x2 | 1.90 | 2.00 | 2.10 | 0.075 | 0.079 | 0.083 |
| y1 | 1.60 | 1.65 | 1.70 | 0.063 | 0.065 | 0.067 |
| y2 | 4.65 | 4.70 | 4.75 | 0.183 | 0.185 | 0.187 |
| z1 | 2.80 | 2.90 | 3.00 | 0.110 | 0.114 | 0.118 |




Rectifier


Fig. 1 Forward current vs. voltage drop per diode




Fig. 2 Surge overload current vs. time per diode




 Fig. 3 I^2t vs. time per diode


Fig. 4 Power dissipation vs. forward current and ambient temperature per diode




Fig. 5 Max. forward current vs. case temperature per diode




Fig. 6 Transient thermal impedance junction to case vs. time per diode

 Constants for Z_{thJC} calculation:

| i | R_{th} (K/W) | t_i (s) |
|---|----------------|-----------|
| 1 | 0.302 | 0.002 |
| 2 | 1.252 | 0.032 |
| 3 | 1.582 | 0.227 |
| 4 | 1.164 | 0.820 |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[IXYS:](#)

[DMA40U1800GU](#)