

IGBT - Field Stop, Trench

650 V, 40 A

FGH40T65SQD

Description

Using novel field stop IGBT technology, onsemi's new series of field stop 4th generation IGBTs offer the optimum performance for solar inverter, UPS, welder, telecom, ESS and PFC applications where low conduction and switching losses are essential.



Features

- Max Junction Temperature 175°C
- Positive Temperature Co-efficient for Easy Parallel Operating
- High Current Capability
- Low Saturation Voltage: $V_{CE(sat)} = 1.6$ V (Typ.) @ $I_C = 40$ A
- 100% of the Parts Tested for I_{LM}
- High Input Impedance
- Fast Switching
- Tighten Parameter Distribution
- This Device is Pb-Free and is RoHS Compliant

Applications


- Solar Inverter, UPS, Welder, Telecom, ESS, PFC

V_{CES}	I_C
650 V	40 A



TO-247-3LD
CASE 340CH

MARKING DIAGRAM



\$Y = onsemi Logo
 &Z = Assembly Plant Code
 &3 = Numeric Date Code
 &K = Lot Code
 FGH40T65SQD = Specific Device Code

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

FGH40T65SQD

ABSOLUTE MAXIMUM RATINGS

Symbol	Description		FGH40T65SQD-F155	Unit
V_{CES}	Collector to Emitter Voltage		650	V
V_{GES}	Gate to Emitter Voltage		±20	V
	Transient Gate to Emitter Voltage		±30	V
I_C	Collector Current	$T_C = 25^\circ\text{C}$	80	A
		$T_C = 100^\circ\text{C}$	40	A
I_{LM} (Note 1)	Pulsed Collector Current	$T_C = 25^\circ\text{C}$	160	A
I_{CM} (Note 2)	Pulsed Collector Current		160	A
I_F	Diode Forward Current	$T_C = 25^\circ\text{C}$	40	A
	Diode Forward Current	$T_C = 100^\circ\text{C}$	20	A
I_{FM} (Note 2)	Pulsed Diode Maximum Forward Current		160	A
P_D	Maximum Power Dissipation	$T_C = 25^\circ\text{C}$	238	W
		$T_C = 100^\circ\text{C}$	119	W
T_J	Operating Junction Temperature		-55 to +175	°C
T_{STG}	Storage Temperature Range		-55 to +175	°C
T_L	Maximum Lead Temp. for Soldering Purposes, 1/8" from Case for 5 Seconds		300	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. $V_{CC} = 400$ V, $V_{GE} = 15$ V, $I_C = 160$ A, $R_G = 22$ Ω, Inductive Load.
2. Repetitive rating: Pulse width limited by max. junction temperature.

THERMAL CHARACTERISTICS

Symbol	Parameter	FGH40T65SQD-F155	Unit
$R_{\theta JC}$ (IGBT)	Thermal Resistance, Junction to Case, Max.	0.63	°C/W
$R_{\theta JC}$ (Diode)	Thermal Resistance, Junction to Case, Max.	1.71	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient, Max.	40	°C/W

PACKAGE MARKING AND ORDERING INFORMATION

Device Marking	Device	Package	Reel Size	Tape Width	Qty per Tube
FGH40T65SQD	FGH40T65SQD-F155	TO-247-3LD	-	-	30

FGH40T65SQD

ELECTRICAL CHARACTERISTICS OF THE IGBT ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
BV_{CES}	Collector to Emitter Breakdown Voltage	$\text{V}_{\text{GE}} = 0 \text{ V}$, $\text{I}_C = 1 \text{ mA}$	650	–	–	V
$\Delta \text{BV}_{\text{CES}} / \Delta T_J$	Temperature Coefficient of Breakdown Voltage	$\text{V}_{\text{GE}} = 0 \text{ V}$, $\text{I}_C = 1 \text{ mA}$	–	0.6	–	$\text{V}/^\circ\text{C}$
I_{CES}	Collector Cut-Off Current	$\text{V}_{\text{CE}} = \text{V}_{\text{CES}}$, $\text{V}_{\text{GE}} = 0 \text{ V}$	–	–	250	μA
I_{GES}	G-E Leakage Current	$\text{V}_{\text{GE}} = \text{V}_{\text{GES}}$, $\text{V}_{\text{CE}} = 0 \text{ V}$	–	–	± 400	nA
ON CHARACTERISTICS						
$\text{V}_{\text{GE}(\text{th})}$	G-E Threshold Voltage	$\text{I}_C = 40 \text{ mA}$, $\text{V}_{\text{CE}} = \text{V}_{\text{GE}}$	2.6	4.5	6.4	V
$\text{V}_{\text{CE}(\text{sat})}$	Collector to Emitter Saturation Voltage	$\text{I}_C = 40 \text{ A}$, $\text{V}_{\text{GE}} = 15 \text{ V}$	–	1.6	2.1	V
		$\text{I}_C = 40 \text{ A}$, $\text{V}_{\text{GE}} = 15 \text{ V}$, $T_C = 175^\circ\text{C}$	–	1.92	–	V
DYNAMIC CHARACTERISTICS						
C_{ies}	Input Capacitance	$\text{V}_{\text{CE}} = 30 \text{ V}$, $\text{V}_{\text{GE}} = 0 \text{ V}$, $f = 1\text{MHz}$	–	2620	–	pF
C_{oes}	Output Capacitance		–	60	–	pF
C_{res}	Reverse Transfer Capacitance		–	9	–	pF
SWITCHING CHARACTERISTICS						
$\text{T}_{\text{d}(\text{on})}$	Turn-On Delay Time	$\text{V}_{\text{CC}} = 400 \text{ V}$, $\text{I}_C = 10 \text{ A}$, $\text{R}_G = 6 \Omega$, $\text{V}_{\text{GE}} = 15 \text{ V}$, Inductive Load, $T_C = 25^\circ\text{C}$	–	16.4	–	ns
T_r	Rise Time		–	4.8	–	ns
$\text{T}_{\text{d}(\text{off})}$	Turn-Off Delay Time		–	86.4	–	ns
T_f	Fall Time		–	8.8	–	ns
E_{on}	Turn-On Switching Loss		–	138	–	μJ
E_{off}	Turn-Off Switching Loss		–	52	–	μJ
E_{ts}	Total Switching Loss		–	190	–	μJ
$\text{T}_{\text{d}(\text{on})}$	Turn-On Delay Time	$\text{V}_{\text{CC}} = 400 \text{ V}$, $\text{I}_C = 20 \text{ A}$, $\text{R}_G = 6 \Omega$, $\text{V}_{\text{GE}} = 15 \text{ V}$, Inductive Load, $T_C = 25^\circ\text{C}$	–	17.6	–	ns
T_r	Rise Time		–	9.6	–	ns
$\text{T}_{\text{d}(\text{off})}$	Turn-Off Delay Time		–	80	–	ns
T_f	Fall Time		–	8.8	–	ns
E_{on}	Turn-On Switching Loss		–	329	–	μJ
E_{off}	Turn-Off Switching Loss		–	84	–	μJ
E_{ts}	Total Switching Loss		–	413	–	μJ
$\text{T}_{\text{d}(\text{on})}$	Turn-On Delay Time	$\text{V}_{\text{CC}} = 400 \text{ V}$, $\text{I}_C = 10 \text{ A}$, $\text{R}_G = 6 \Omega$, $\text{V}_{\text{GE}} = 15 \text{ V}$, Inductive Load, $T_C = 175^\circ\text{C}$	–	14.4	–	ns
T_r	Rise Time		–	6.4	–	ns
$\text{T}_{\text{d}(\text{off})}$	Turn-Off Delay Time		–	99.2	–	ns
T_f	Fall Time		–	8	–	ns
E_{on}	Turn-On Switching Loss		–	269	–	μJ
E_{off}	Turn-Off Switching Loss		–	132	–	μJ
E_{ts}	Total Switching Loss		–	401	–	μJ

FGH40T65SQD

ELECTRICAL CHARACTERISTICS OF THE IGBT ($T_C = 25^\circ\text{C}$ unless otherwise noted) (continued)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
SWITCHING CHARACTERISTICS						
$T_{d(on)}$	Turn-On Delay Time	$V_{CC} = 400 \text{ V}, I_C = 20 \text{ A}, R_G = 6 \Omega, V_{GE} = 15 \text{ V}$, Inductive Load, $T_C = 175^\circ\text{C}$	–	16	–	ns
T_r	Rise Time		–	11.2	–	ns
$T_{d(off)}$	Turn-Off Delay Time		–	91.2	–	ns
T_f	Fall Time		–	8	–	ns
E_{on}	Turn-On Switching Loss		–	581	–	μJ
E_{off}	Turn-Off Switching Loss		–	237	–	μJ
E_{ts}	Total Switching Loss		–	818	–	μJ
Q_g	Total Gate Charge	$V_{CE} = 400 \text{ V}, I_C = 40 \text{ A}, V_{GE} = 15 \text{ V}$	–	80	–	nC
Q_{ge}	Gate to Emitter Charge		–	15	–	nC
Q_{gc}	Gate to Collector Charge		–	20	–	nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

ELECTRICAL CHARACTERISTICS OF THE DIODE ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Test Conditions		Min	Typ	Max	Unit	
V_{FM}	Diode Forward Voltage	$I_F = 20 \text{ A}$	$T_C = 25^\circ\text{C}$	–	2.2	2.8	V	
			$T_C = 175^\circ\text{C}$	–	1.94	–		
E_{rec}	Reverse Recovery Energy	$I_F = 20 \text{ A}, dI_F/dt = 200 \text{ A}/\mu\text{s}$	$T_C = 175^\circ\text{C}$	–	50	–	μJ	
T_{rr}	Diode Reverse Recovery Time		$T_C = 25^\circ\text{C}$	–	31.8	–	ns	
			$T_C = 175^\circ\text{C}$	–	192	–		
Q_{rr}	Diode Reverse Recovery Charge		$T_C = 25^\circ\text{C}$	–	50.6	–	nC	
			$T_C = 175^\circ\text{C}$	–	699	–		

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

TYPICAL CHARACTERISTICS




Figure 1. Typical Output Characteristics




Figure 2. Typical Output Characteristics




Figure 3. Typical Saturation Voltage Characteristics




Figure 4. Saturation Voltage vs. Case Temperature at Variant Current Level




Figure 5. Saturation Voltage vs. V_{GE}




Figure 6. Saturation Voltage vs. V_{GE}

TYPICAL CHARACTERISTICS (Continued)




Figure 7. Capacitance Characteristics




Figure 8. Gate Charge Characteristics




Figure 9. Turn-on Characteristics vs. Gate Resistance




Figure 10. Turn-off Characteristics vs. Gate Resistance




Figure 11. Switching Loss vs. Gate Resistance




Figure 12. Turn-on Characteristics vs. Collector Current

TYPICAL CHARACTERISTICS (Continued)






Figure 15. Load Current vs. Frequency




Figure 16. SOA Characteristics




Figure 17. Forward Characteristics




Figure 18. Reverse Recovery Current

TYPICAL CHARACTERISTICS (Continued)




Figure 19. Reverse Recovery Time




Figure 20. Stored Charge




Figure 21. Transient Thermal Impedance of IGBT






Figure 22. Transient Thermal Impedance of Diode



NOTES: UNLESS OTHERWISE SPECIFIED.

- A. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
- B. ALL DIMENSIONS ARE IN MILLIMETERS.
- C. DRAWING CONFORMS TO ASME Y14.5 - 2009.
- D. DIMENSION A1 TO BE MEASURED IN THE REGION DEFINED BY L1.
- E. LEAD FINISH IS UNCONTROLLED IN THE REGION DEFINED BY L1.

**GENERIC
MARKING DIAGRAM***



XXXX = Specific Device Code

A = Assembly Location

Y = Year

WW = Work Week

G = Pb-Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "•", may or may not be present. Some products may not follow the Generic Marking.

DIM	MILLIMETERS		
	MIN	NOM	MAX
A	4.58	4.70	4.82
A1	2.29	2.475	2.66
A2	1.40	1.50	1.60
D	20.32	20.57	20.82
E	15.37	15.62	15.87
E2	4.96	5.08	5.20
e	~	5.56	~
L	19.75	20.00	20.25
L1	3.69	3.81	3.93
ØP	3.51	3.58	3.65
Q	5.34	5.46	5.58
S	5.34	5.46	5.58
b	1.17	1.26	1.35
b2	1.53	1.65	1.77
b4	2.42	2.54	2.66
c	0.51	0.61	0.71
D1	13.08	~	~
D2	0.51	0.93	1.35
E1	12.81	~	~
ØP1	6.61	6.73	6.85

DOCUMENT NUMBER:	98AON13853G	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	TO-247-3LD	PAGE 1 OF 1

onsemi and **onsemi** are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, **ONSEMI**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[onsemi](#):

[FGH40T65SQD-F155](#)