

REV	2		1	
	CONTENT		CHK	DATE
V0.0	CONTENT		MYZ	21.05.21

Electrical :

- | | | |
|--|---------------|------------------------|
| | UL | IEC |
| 1.Rated Voltage : | 300V | 250V |
| 2.Rated Current : | 8A | 5A |
| 3.Wire Range: | 28-16AWG | 0.5-1.5mm ² |
| 4.Stripping Length : | 7-8mm | |
| 5.Withstanding Voltage : | AC1600V/1Min. | |
| 6.Operating Temperature : | -40°C~+105°C | |
| 7.RoHS Compliance | | |
| 8.Safty Approval : | cULus CE | |
| 9."★" is the key quality control point | | |

15EGTKDM - 3.81 -XXP - X X - 00

① ② ③ ④ ⑤ ⑥

① Sereies NO. ④ 1 Single Pitch
2 Double Pitch

② Pitch ⑤ Color: 1 Grey
2 Blue
3 Black
4 Green
5 Orange
6 Red
7 Transparent
8 Yellow
9 White

⑥ Customer Request: 00-- Standard

6	Screw	XXXXXX	2	STEEL	Zn Plated
5	Button	XXXXXX	P	POM	UL94HB
4	Spring	XXXXXX	P	Srainless steel	/
3	Clamp	XXXXXX	P		