

Features

- Semi-shielded construction
- Inductance range: 0.5 to 330 µH
- Rated current up to 12 A
- AEC-Q200 compliant
- RoHS compliant* and halogen free**

Additional Information

Click these links for more information:











LIBRARY

PRODUCT TECHNICAL INVENTORY SAMPLES

CONTACT


BOURNS

SRN8040TA Series - Semi-shielded Power Inductors

Electrical Specifications @ 25 °C

	Inductance @ 1 MHz / 1 V		Q (Min.)	SRF (MHz)	DCR (mΩ)	Irms (A)	Isat (A)
Bourns Part No.	L (μH)	Tol. %	@ 1 MHz	Typ.	±20 %	Typ.	Typ.
SRN8040TA-R50Y	0.5	± 30	20	165	5.5	12.00	17.00
SRN8040TA-1R0Y	1.0	± 30	15	85	8.2	8.50	13.80
SRN8040TA-1R2Y	1.2	± 30	15	80	8.2	8.30	12.80
SRN8040TA-1R4Y	1.4	± 30	15	78	10	8.20	11.80
SRN8040TA-1R5Y	1.5	± 30	15	66	10	8.00	11.50
SRN8040TA-2R0Y	2.0	± 30	15	61	11	7.50	10.20
SRN8040TA-2R2Y	2.2	± 30	15	57	11.5	7.40	9.80
SRN8040TA-3R3Y	3.3	± 30	15	48	15	6.60	8.00
SRN8040TA-3R6Y	3.6	± 30	15	42	15	6.40	7.60
SRN8040TA-4R7M	4.7	± 20	15	38	19.5	5.80	6.70
SRN8040TA-5R6M	5.6	± 20	15	33	22	5.40	6.20
SRN8040TA-6R8M	6.8	± 20	15	29	25	5.10	5.60
SRN8040TA-8R2M	8.2	± 20	15	27	30	4.80	5.30
SRN8040TA-100M	10	± 20	15	25	33	4.60	5.00
SRN8040TA-150M	15	± 20	12	20	50	3.60	4.00
SRN8040TA-220M	22	± 20	12	18	73	2.90	3.10
SRN8040TA-330M	33	± 20	12	15	100	2.30	2.60
SRN8040TA-470M	47	± 20	12	12	135	2.00	2.20
SRN8040TA-560M	56	± 20	12	10.5	160	1.75	1.90
SRN8040TA-680M	68	± 20	12	9.5	205	1.65	1.75
SRN8040TA-820M	82	± 20	12	8.5	230	1.40	1.60
SRN8040TA-101M	100	± 20	10	8	300	1.20	1.45
SRN8040TA-121M	120	± 20	10	7.5	350	1.10	1.30
SRN8040TA-151M	150	± 20	10	7	410	0.98	1.20
SRN8040TA-181M	180	± 20	10	6.5	490	0.91	1.04
SRN8040TA-221M	220	± 20	10	5.5	610	0.85	0.99
SRN8040TA-331M	330	± 20	10	5	850	0.70	0.75
SRN8040TA-471M	470	± 20	10	3.4	1300	0.63	0.60

Electrical Schematic




How to Order

SRN8040TA - 100M

Model Value Code (see table)

Recommended Layout





CALIFORNIA WARNING: Can expose you to lead, a carcinogen and reproductive toxicant. See www.P65Warnings.ca.gov

- RoHS Directive 2015/863, Mar 31, 2015 and Annex.
- Bourns considers a product to be "halogen free" if (a) the Bromine (Br) content is 900 ppm or less; (b) the Chlorine (CI) content is 900 ppm or less; and (c) the total Bromine (Br) and Chlorine (CI) content is 1500 ppm or less. Specifications are subject to change without notice. Users should verify actual device performance in their specific applications. The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

General Specifications

Operating Temp. -55 °C to +125 °C (Temperature rise included) Storage Temperature.. -55 °C to +125 °C Temperature Rise40 °C at rated Irms Rated Current Inductance drops 30 % at Isat


Failure In Time (FIT)......24.7/109 hours Mean Time Between Failures (MTBF)


......40.4 x 10⁶ hours Moisture Sensitivity Level.....1 ESD Classification (HBM).....N/A


Materials

Core	Ferrite
Wire	Enameled copper
Terminal Finish	Sn
Coating	.Magnetic epoxy resin
Packaging 100	0 pcs. per 13-inch reel

Product Dimensions









(INCHES)

SRN8040TA Series - Semi-shielded Power Inductors **BOURNS**





SRN8040TA Series - Semi-shielded Power Inductors **BOURNS**





SRN8040TA Series – Semi-shielded Power Inductors

Inductance vs. Current (continued)











Soldering Profile



SRN8040TA Series - Semi-shielded Power Inductors **BOURNS**®

Packaging Specifications



BOURNS®

Americas: Tel: +1 951-781-5500 • Email: americus@bourns.com

Mexico: Tel: +52-614-478-0400 • Email: mexicus@bourns.com

Asia: Tel: +886-2-2562-4117 • Email: asiacus@bourns.com

EMEA: Tel: +36 88 885 877 • Email: eurocus@bourns.com

www.bourns.com

REV. 07/25

Legal Disclaimer Notice

BOURNS

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain types of applications are based on Bourns' knowledge of typical requirements in generic applications. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Users should always verify the actual performance of the Bourns® product in their specific devices and applications, and make their own independent judgments regarding the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., IATF 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification. Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in nuclear, lifesaving, life-critical or life-sustaining applications, nor in any other applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage. Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any Bourns® products in such unauthorized applications might not be safe and thus is at the user's sole risk. Life-critical applications include devices identified by the U.S. Food and Drug Administration as Class III devices and generally equivalent classifications outside of the United States.

Bourns expressly identifies those Bourns® standard products that are suitable for use in automotive applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard products in an automotive application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk. If Bourns expressly identifies a sub-category of automotive application in the data sheet for its standard products (such as infotainment or lighting), such identification means that Bourns has reviewed its standard product and has determined that if such Bourns® standard product is considered for potential use in automotive applications, it should only be used in such sub-category of automotive applications. Any reference to Bourns® standard product in the data sheet as compliant with the AEC-Q standard or "automotive grade" does not by itself mean that Bourns has approved such product for use in an automotive application.

Bourns® standard products are not tested to comply with United States Federal Aviation Administration standards generally or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aircraft or space applications. Bourns expressly identifies Bourns® standard products that are suitable for use in aircraft or space applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard product in an aircraft or space application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Users shall not sell, transfer, export or re-export any Bourns® products or technology for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology in any facility which engages in activities relating to such devices. The foregoing restrictions apply to all uses and applications that violate national or international prohibitions, including embargos or international regulations. Further, Bourns® products and Bourns technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products may not, without prior authorization from Bourns and/or the U.S. Government, be resold, transferred, or re-exported to any party not eligible to receive U.S. commodities, software, and technical data.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties, including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: http://www.bourns.com/legal/disclaimers-terms-and-policies

PDF: http://www.bourns.com/docs/Legal/disclaimer.pdf

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Bourns:

 SRN8040TA-121M
 SRN8040TA-331M
 SRN8040TA-6R8M
 SRN8040TA-1R4Y
 SRN8040TA-150M
 SRN8040TA-331M

 330M
 SRN8040TA-101M
 SRN8040TA-680M
 SRN8040TA-181M
 SRN8040TA-1R5Y
 SRN8040TA-470M

 SRN8040TA-220M
 SRN8040TA-2R2Y
 SRN8040TA-3R3Y
 SRN8040TA-5R6M
 SRN8040TA-820M
 SRN8040TA-100M

 151M
 SRN8040TA-750Y
 SRN8040TA-221M
 SRN8040TA-4R7M
 SRN8040TA-1R0Y
 SRN8040TA-100M

 SRN8040TA-560M
 SRN8040TA-2R0Y
 SRN8040TA-471M
 SRN8040TA-8R2M
 SRN8040TA-3R6Y