




NPN General Purpose Amplifier



SOT-323

Features

- Epoxy meets UL-94 V-0 flammability rating and halogen free
- Moisture Sensitivity Level 1
- Part no. with suffix "Q" means AEC-Q101 qualified

Applications

- NPN General purpose switching and amplification

Mechanical Data

- Case: SOT-323
- Terminals: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- Marking:

BC817-16WQ	6A
BC817-25WQ	6B
BC817-40WQ	6C

■ Maximum Ratings (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Value
Collector-Base Voltage	V_{CEO}	V	45
Collector-Emitter Voltage	V_{CBO}	V	50
Emitter-Base Voltage	V_{EBO}	V	5
Collector Current -Continuous	I_C	mA	500
Total Device Dissipation	P_D	mW	200
Junction Temperature	T_j	°C	-55 to +150
Storage Temperature	T_{STG}	°C	-55 to +150

■ Electrical Characteristics (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Conditions	Min	Typ	Max
Collector-base breakdown voltage	V_{CEO}	V	$I_C=10mA, I_B=0$	45		
Collector-emitter breakdown voltage	V_{CBO}	V	$I_C=10\mu A, I_E=0$	50		
Emitter-base breakdown voltage	V_{EBO}	V	$I_E=1\mu A, I_C=0$	5		
Collector-base cut-off current	I_{EBO}	μA	$V_{EB}=4V, I_C=0$			0.1
Emitter-base cut-off current	I_{CBO}	μA	$V_{CB}=45V, I_E=0$			0.1
DC current gain	h_{FE}		BC817-16WQ	100		250
			BC817-25WQ	160		400
			BC817-40WQ	250		600
DC current gain	h_{FE}		$V_{CE}=1V, I_C=500mA$	40		
Collector-emitter saturation voltage	$V_{CE(sat)}$	V	$I_C=500mA, I_B=50mA$			0.7
Base-emitter saturation voltage	$V_{BE(sat)}$	V	$I_C=500mA, I_B=50mA$			1.2



BC817-16WQ THRU BC817-40WQ

Other Characteristics (Ta=25°C unless otherwise noted)


Item	Symbol	Unit	Conditions	Min	Typ	Max
Transition frequency	f_T	MHz	$V_{CE}=5V, I_C=10mA, f=100MHz$	100		

Ordering Information (Example)


PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
BC817-16WQ THRU BC817-40WQ	F2	Approximate 0.005	3000	30000	120000	7" reel

Characteristics(Typical)


Static Characteristic




DC Current Gain



Collector-Emitter Saturation Voltage




Base-Emitter Saturation Voltage






BC817-16WQ THRU BC817-40WQ






BC817-16WQ THRU BC817-40WQ

■ SOT-323 Package Outline Dimensions



SYMBOL	DIMENSIONS			
	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.035	0.043	0.900	1.100
A1	0.000	0.004	0.000	0.100
A2	0.035	0.039	0.900	1.000
b	0.006	0.016	0.150	0.400
c	0.004	0.010	0.100	0.250
D	0.071	0.087	1.800	2.200
E	0.045	0.053	1.150	1.350
E1	0.085	0.096	2.150	2.450
e	0.026TYP		0.650TYP	
e1	0.047	0.055	1.200	1.400
L	0.021REF		0.525REF	
L1	0.010	0.018	0.260	0.460
θ	0°	8°	0°	8°

■ SOT-323 Suggested Pad Layout



Unit: mm



BC817-16WQ THRU BC817-40WQ

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, life-saving, life-sustaining, or military. Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.