



Surface Mount Super Fast Recovery Rectifier



Features

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- High forward surge capability
- Super Fast reverse recovery time
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C

Typical Applications

For use in high frequency rectification of power supplies, inverters, converters, and freewheeling diodes for consumer, and telecommunication.

Mechanical Data

- **Package:** DO-214AC(SMA)
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

■ Maximum Ratings (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MURS220A	MURS240A	MURS260A
Device marking code			MURS220A	MURS240A	MURS260A
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	V	200	400	600
Maximum RMS Voltage	V _{RMS}	V	140	280	420
Maximum DC blocking Voltage	V _{DC}	V	200	400	600
Average rectified output current @60Hz sine wave, resistance load, TL (Fig.1)	I _O	A	2.0		
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, T _j =25°C	I _{FSM}	A	50		
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, T _j =25°C			100		
Current squared time @1ms≤t≤8.3ms T _j =25°C, Rating of per diode	I ² t	A ² s	10.375		
Typical junction capacitance @Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	C _j	pF	25	25	24
Storage temperature	T _{stg}	°C	-55 ~ +150		
Junction temperature	T _j	°C	-55 ~ +150		



MURS220A THRU MURS260A

■Electrical Characteristics (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	MURS220A	MURS240A	MURS260A
Maximum instantaneous forward voltage drop per diode	V _F	V	I _{FM} =2.0A	0.92	1.25	
Maximum reverse recovery time	t _{rr}	ns	I _F =0.5A, I _R =1.0A, I _{rr} =0.25A	25	50	
Maximum DC reverse current at rated DC blocking voltage per diode	I _R	μA	T _J =25°C	5.0		
			T _J =125°C	50		

■Dynamic Characteristics

◆ MURS220A

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
Reverse Recovery Time	T _{RR}	ns	T _j =25°C	I _F =1A, di/dt=-50A/us V _{RM} =30V	-	26	-
			T _j =25°C	I _F =2A di/dt=-200A/us V _{RM} =100V	-	23	-
			T _j =125°C		-	30	-
Peak recovery current	I _{RRM}	A	T _j =25°C		-	3.1	-
			T _j =125°C		-	5.0	-
Reverse recovery charge	Q _{rr}	nC	T _j =25°C		-	35.4	-
			T _j =125°C		-	73.8	-
Non-repetitive avalanche energy	E _{AS}	mJ	T _j =25°C	I _R =1.8 A, L=15 mH	24.3	-	-

◆ MURS240A

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
Reverse Recovery Time	T _{RR}	ns	T _j =25°C	I _F =1A, di/dt=-50A/us V _{RM} =30V	-	35	-
			T _j =25°C	I _F =2A di/dt=-200A/us V _{RM} =200V	-	30	-
			T _j =125°C		-	45	-
Peak recovery current	I _{RRM}	A	T _j =25°C		-	3.7	-
			T _j =125°C		-	5.8	-
Reverse recovery charge	Q _{rr}	nC	T _j =25°C		-	55.4	-
			T _j =125°C		-	130.6	-
Non-repetitive avalanche energy	E _{AS}	mJ	T _j =25°C	I _R =0.5A, L=15 mH	1.9	-	-

◆ MURS260A

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
Reverse Recovery Time	T _{RR}	ns	T _j =25°C	I _F =1A, di/dt=-50A/us V _{RM} =30V	-	50	-
			T _j =25°C	I _F =2A di/dt=-200A/us V _{RM} =400V	-	43	-
			T _j =125°C		-	66	-
Peak recovery current	I _{RRM}	A	T _j =25°C		-	5.0	-
			T _j =125°C		-	7.4	-
Reverse recovery charge	Q _{rr}	nC	T _j =25°C		-	105.9	-
			T _j =125°C		-	243.8	-
Non-repetitive avalanche energy	E _{AS}	mJ	T _j =25°C	I _R =0.5A, L=15 mH	1.9	-	-



MURS220A THRU MURS260A

■ Thermal Characteristics (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MURS220A	MURS240A	MURS260A
Typical Thermal resistance	R θ J-A ⁽¹⁾	°C/W	65		
	R θ J-L ⁽¹⁾		25		
	R θ J-C ⁽¹⁾		20		

Note:

(1) Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.2" x 0.2" (5.0 mm x 5.0 mm) copper pad areas

■ Characteristics (Typical)

FIG.1: Io-TL Curve




FIG.2: Forward Surge Current Capability




FIG.3: Typical Forward Voltage






FIG.4: Typical Reverse Characteristics





MURS220A THRU MURS260A


FIG.5: Diagram of circuit and Testing wave form of reverse recovery time



■ Ordering Information (Example)

PREFERRED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MURS220A-MURS260A	F1	Approximate 0.059	5000	10000	80000	13" reel
MURS220A-MURS260A	F2	Approximate 0.059	7500	15000	120000	13" reel
MURS220A-MURS260A	F3	Approximate 0.059	7500	15000	60000	13" reel
MURS220A-MURS260A	F4	Approximate 0.059	1800	14400	57600	7" reel
MURS220A-MURS260A	F5	Approximate 0.059	2000	16000	64000	7" reel
MURS220A-MURS260A	F6	Approximate 0.059	5000	10000	100000	13" reel

■ Outline Dimensions




DO-214AC(SMA)		
Dim	Min	Max
A	1.25	1.58
B	2.40	2.83
C	4.06	4.75
D	1.90	2.30
E	4.93	5.28
F	0.76	1.41
G	0.08	0.20
H	0.15	0.31



MURS220A THRU MURS260A

■Suggested Pad Layout



DO-214AC(SMA)	
Dim	Millimeters
P1	4.00
P2	1.50
P3	6.50
Q1	2.50
Q2	1.70



MURS220A THRU MURS260A

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.