




P-Channel Enhancement Mode Field Effect Transistor



SOT-323



Product Summary

- V_{DS} -20V
- I_D -2.0A
- $R_{DS(ON)}$ (at $V_{GS}=-4.5V$) < 130 mohm
- $R_{DS(ON)}$ (at $V_{GS}=-2.5V$) < 170 mohm
- $R_{DS(ON)}$ (at $V_{GS}=-1.8V$) < 250 mohm

General Description

- Trench Power LV MOSFET technology
- Low $R_{DS(ON)}$
- Low Gate Charge

Applications

- Video monitor
- Power management

■ Absolute Maximum Ratings ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter		Symbol	Maximum	Unit
Drain-source Voltage		V_{DS}	-20	V
Gate-source Voltage		V_{GS}	± 10	V
Drain Current	$T_A=25^\circ\text{C}$ @ Steady State	I_D	-2.0	A
	$T_A=70^\circ\text{C}$ @ Steady State		-1.6	
Pulsed Drain Current ^A		I_{DM}	-8	A
Total Power Dissipation @ $T_A=25^\circ\text{C}$		P_D	0.25	W
Thermal Resistance Junction-to-Ambient ^B		$R_{\theta JA}$	500	$^\circ\text{C}/\text{W}$
Junction and Storage Temperature Range		T_J, T_{STG}	-55~+150	$^\circ\text{C}$

■ Ordering Information

PREFERRED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
YJL2101W	F2	TS1.	3000	30000	120000	7" reel



YJL2101W

■ Electrical Characteristics (T_J=25℃ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Static Parameter						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} = 0V, I _D =-250μA	-20			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =-20V,V _{GS} =0V,T _C =25℃			-1	μA
Gate-Body Leakage Current	I _{GSS}	V _{GS} = ± 10V, V _{DS} =0V			± 100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D =-250μA	-0.4	-0.62	-1.0	V
Static Drain-Source On-Resistance	R _{DS(ON)}	V _{GS} = -4.5V, I _D =-1.5A		100	130	mΩ
		V _{GS} = -2.5V, I _D =-1.2A		135	170	
		V _{GS} = -1.8V, I _D =-1.0A		175	250	
Diode Forward Voltage	V _{SD}	I _S =-2.0A,V _{GS} =0V		-0.8	-1.2	V
Dynamic Parameters						
Input Capacitance	C _{iss}	V _{DS} =-10V,V _{GS} =0V,f=1MHZ		327		pF
Output Capacitance	C _{oss}			62		
Reverse Transfer Capacitance	C _{rss}			55		
Switching Parameters						
Total Gate Charge	Q _g	V _{GS} =-4.5V,V _{DS} =-10V,I _D =-1.0A		4.5		nC
Gate Source Charge	Q _{gs}			0.85		
Gate Drain Charge	Q _{gd}			1.4		
Turn-on Delay Time	t _{D(on)}	V _{GS} =-4.5V,V _{DD} =-10V, I _D =-1A, R _{GEN} =2.5Ω		6		ns
Turn-on Rise Time	t _r			30		
Turn-off Delay Time	t _{D(off)}			45		
Turn-off Fall Time	t _f			46		

A. A.Pulse Test: Pulse Width≤300us,Duty cycle ≤2%.

B. Device mounted on FR-4 PCB, 1 inch x 0.85 inch x 0.062 inch.



■ Typical Performance Characteristics




Figure1. Output Characteristics




Figure2. Transfer Characteristics




Figure3. Capacitance Characteristics




Figure4. Gate Charge




Figure5. Drain-Source on Resistance




Figure6. Drain-Source on Resistance




Figure7. Safe Operation Area






Figure8. Drain Current vs Ambient temperature




■ SOT-323 Package Information




TOP VIEW



SIDE VIEW



SIDE VIEW



SUGGESTED SOLDER PAD LAYOUT

SYMBOL	DIMENSIONS					
	INCHES			Millimeter		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	0.035	----	0.043	0.900	----	1.100
A1	0.000	----	0.004	0.000	----	0.100
A2	0.035	0.037	0.039	0.900	0.950	1.000
b	0.006	0.012	0.016	0.150	0.300	0.400
c	0.004	----	0.010	0.100	----	0.250
D	0.071	0.079	0.087	1.800	2.000	2.200
E	0.045	0.049	0.053	1.150	1.250	1.350
E1	0.085	0.091	0.096	2.150	2.300	2.450
e	0.026TYP			0.650TYP		
e1	0.047	0.051	0.055	1.200	1.300	1.400
L	0.021REF			0.525REF		
L1	0.010	0.014	0.018	0.260	0.360	0.460
θ	0°	----	8°	0°	----	8°

NOTE:

- 1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
- 2.TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.
- 3.THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.