


Data sheet

Commercial Art.No.: 5D.S06.2455.6

test disconnect terminal WTN 6 TD BL

test disconnect terminal WTN 6 TD BL rated voltage 800 V, rated current 41 A, screw connection, number of levels 1, number of clamp positions per level 2, nominal cross section 6 mm², connectable conductor cross section fine stranded without cable end sleeve 0,5mm² - 6mm², mounting method DIN rail (top hat rail), color blue, width/grid dimension 8 mm, inflammability class of insulation material acc. with ul94 V0



Commercial Art.No.	5D.S06.2455.6
EAN	4049088725302
Order Unit	50

certificates / approvals



Technical data

general

nominal cross section	6 mm ²
color	blue
number of levels	1
number of clamp positions per level	2
width/grid dimension	8 mm
insulating housing	PA
inflammability class of insulation material acc. with UL94	V0
mounting method	DIN rail (top hat rail)

technical data

rated current	41 A
rated voltage	800 V
rated impulse voltage	8 kV
pollution degree	3
closing plate required	yes
type of insulation material	thermoplastic
length	72.5 mm
width	8 mm

connection data

connection type	screw connection
connection type 1	screw connection
connection type 2	screw connection
minimum cross section solid	0.5 mm ²
maximum cross section solid	10 mm ²

minimum cross section fine stranded	0.5 mm ²
maximum cross section fine stranded	6 mm ²
minumum conductor cross section (flex., stranded) with cable end sleeve	0.5 mm ²
maximum conductor cross section (flex., stranded) with cable end sleeve	6 mm ²
wire strip length	10 mm
torque conductor mounting	1.2 Nm

technical data UL/CSA

cross section UL	20-8 AWG
voltage UL	300 V
current factory wiring	42 A
current field wiring	42 A
cross section CSA	20-8 AWG
voltage CSA	300 V
current CSA	42 A

additional data

integrated test socket	no
------------------------	----

classification


ETIM 9.0	EC000902
----------	----------

product compliance

REACH-SVHC conformity status	compliant
------------------------------	-----------

Accessories

Commercial Art.No.:	Article-type description:	Description:
0D.S06.1155.9	partition TW 006 WTN	
0D.S06.1255.9	partition TW 007 WTN	
0D.202.7281.0	marking strips WML 9.8/60	marking strips WML 9.8/60 color white
0D.206.7056.0	marking plate WMP 8-10	marking plate WMP 8-10 modular spacing 8 mm, color white



A
Alle Rechte vorbehalten
All rights reserved
Vertraulichkeitsklasse
Confidentiality Class
Vertraulich
Confidential

B
These dimensions will be especially checked at delivery
Only inspection dimensions
With /E marked dimensions are only valid for internal use

C
Diese Maße werden bei Abnahme besonders geprüft
Ausschließlich Prüfmaße
Mit /E gekennzeichnete Maße sind nur für interne Zwecke gültig

F

Weitere Daten siehe KATALOG oder eKatalog
additional data see CATALOG or eCATALOG
www.wieland-electric.com
eshop.wieland-electric.com

Tolerierung Size ISO 14405 © / Tolerance system Size ISO 14405 ©. (This ISO-standard describes the envelope principle. According to the envelope principle the deviations of form and parallelism are limited by the size tolerances).					ja/yes ☒ Stoffverbots- und Deklarationsliste nach WN 5020.010 ist einzuhalten. Conformity with Wieland document WN 5020.010 e (list of prohibited / declarable hazardous substances) to be declared!					
Freitoleranz nach General tolerance			CAD - Zeichnung, keine manuellen Änderungen CAD - drawing, no manual modifications allowed			1. Verwendung: First Use:		Blatt: 1 von 1 Sheet: 1 of 1		
	/		Werkstoff / Material		Tag/Date	Name		T	Zeichnung Nr. / Drawing No.	Index
	/			gezeichnet drawn	16.09.2025	Sachs (extern)				
	/			Maßstab / Scale		Elektronische Freigabe Electronic Release				
	/			2:1						
	/					Maße in mm / Dimensions are in mm				
	/	Vol.	mm ³	Dfl./Srf.	mm ²	Ersatz für / Replacement for:				
	/				Type	Benennung/Title PRUEFTRENNKLEMME test disc. terminal				
	/									
	/									
	/									
Index	Datum / Blatt Date / Sheet									
Änderung / Revision										

Bestell-Nr. /order no.	Typ /type	Farbe /colour
5D.S06.2455.0	WTN 6 TD	grau / grey
5D.S06.2455.5	WTN 6 TD RT	rot / red
5D.S06.2455.6	WTN 6 TD BL	blau / blue

