


Data sheet

Commercial Art.No.: 5D.202.9055.0

earth terminal WTPN 1.5 PE

earth terminal WTPN 1.5 PE rated voltage 500 V, push-Inconnection//true, number of levels 1, number of clamp positions per level 2, nominal cross section 1.5 mm², connectable conductor crosssection fine stranded without cable end sleeve 0,14mm² - 1,5mm², mounting method DIN rail (top hat rail), color green/yellow, width/griddimension 3.5 mm, inflammability class of insulation material acc. with UL94 V0, terminal blocks for electrical installations yes



Commercial Art.No.	5D.202.9055.0
EAN	4049088719813
Order Unit	100

certificates / approvals



LR

Technical data

general

nominal cross section	1.5 mm ²
color	green/yellow
number of levels	1
number of clamp positions per level	2
width/grid dimension	3.5 mm
insulating housing	PA
inflammability class of insulation material acc. with UL94	V0
mounting method	DIN rail (top hat rail)
terminal blocks for electrical installations	yes
Anschlussart	push-In connection//true
Anzahl der Klemmstellen je Etage	2
Montageart	DIN rail (top hat rail)
Brennbarkeitsklasse des Isolierstoffs	V0
Reihenklappen für Installationsverteiler	yes

technical data

rated voltage	500 V
rated impulse voltage	6 kV
pollution degree	3
closing plate required	yes
type of insulation material	thermoplastic
length	71.5 mm
width	3.5 mm
height	63 mm

connection data

connection type	push-In connection//true
connection type 1	plug-in connection
connection type 2	spring clamp connection
minimum cross section solid	0.14 mm ²
maximum cross section solid	1.5 mm ²
minimum cross section fine stranded	0.14 mm ²
maximum cross section fine stranded	1.5 mm ²
minumum conductor cross section (flex., stranded) with cable end sleeve	0.25 mm ²
maximum conductor cross section (flex., stranded) with cable end sleeve	0.75 mm ²
wire strip length	10 mm

technical data UL/CSA

cross section UL	26-14 AWG
voltage UL	300 V
cross section CSA	26-14 AWG
voltage CSA	300 V

classification

ETIM 9.0	EC000901
----------	----------

product compliance

REACH-SVHC conformity status	compliant
------------------------------	-----------

Accessories

Commercial Art.No.:	Article-type description:	Description:
0D.202.8055.5	test plug PS 1.5	test plug PS 1.5 number of clamp positions per level 1, mounting methodpluggable, color red, width/grid dimension 3.5 mm, inflammability classof insulation material acc. with ul94 V0
0D.202.8155.5	spacer SPS 1.5	spacer SPS 1.5 length 20 mm, height 27 mm, material plastic, color red,inflammability class of insulation material acc. with ul94 V0
0D.202.1055.0	partition TW 001	partition inflammability class of insulation material acc. with ul94 V0,type of end plate no, thickness 1.5 mm, length 57 mm, color grey
0D.202.2055.0	end plate APWTPN 1.5	end plate inflammability class of insulation material acc. with ul94 V0,type of end plate yes, thickness 2 mm, length 46.5 mm, color grey
0D.202.2055.7	end plate APWTPN 1.5 GN	end plate inflammability class of insulation material acc. with ul94 V0,type of end plate yes, length 46.5 mm, color green
0D.202.7056.0	marking plate WMP 3.5-10	marking plate WMP 3.5-10 modular spacing 3.5 mm, material plastic, colorwhite, length 128 mm, height 76 mm, inflammability class of insulationmaterial acc. with ul94 V0
0D.202.7156.0	marking plate WMP 3.5-5.8	marking plate WMP 3.5-5.8 modular spacing 3.5 mm, material plastic,color white, length 128 mm, height 76 mm, inflammability class ofinsulation material acc. with ul94 V0
0D.202.7281.0	marking strips WML 9.8/60	marking strips WML 9.8/60 material plastic, color white, length 230 mm,height 15.1 mm, inflammability class of insulation material acc. withul94 V0
0D.202.7381.0	marking strips WML 7.4/60	marking strips WML 7.4/60 material plastic, color white, length 230 mm,height 11.4 mm, inflammability class of insulation material acc. withul94 V0

0D.202.7455.0	marking tag ZS 001	marking tag ZS 001 modular spacing 3.5 mm, length 25 mm, height 22.45mm, material plastic, color transparent, inflammability class of insulation material acc. with ul94 V0
0D.202.7555.0	marking tag ZS 002	marking tag ZS 002 modular spacing 12 mm, length 25 mm, height 22.45 mm, material plastic, color transparent, inflammability class of insulation material acc. with ul94 V0