

C981U103MZVDBA7317

Obsolete

C900AC SFTY X1-440 Y2-300, Ceramic, 0.01 uF, 20%, 440 VAC (X1), 300 VAC (Y2), Y5V, 10 mm





The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

Click here for the 3D model.

General Information	
Gruppe	C900AC SFTY X1-440 Y2-300
Typ	Radial Disc
RoHS	Yes
Terminierung	Tin
Ausfallrate	N/A
Zulassungen	VDE, ENEC, UL, cUL
halogenfrei	Yes

Dimensions	
D	15mm MAX
T	5mm MAX
S	10mm +/-1mm
H0	18mm +2/-0mm
F	0.55mm +/-0.1mm

Packaging Specifications	
Verpackung	Ammo
Verpackungsmenge	500

Specifications	
Kapazität	0.01 uF
Kapazitätstoleranz	20%
Sicherheitsspannungsanzeige	440 VAC (X1), 300 VAC (Y2)
Durchschlagsfestigkeit	2,600 VDC
Temperaturbereich	-40/+125°C
Temperaturkoeffizient	Y5V
Verlustfaktor	5%
Isolationswiderstand	10 GOhms
Sicherheitsklasse	X1/Y2

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

© 2006 - 2026 YAGEO